

**100%** Money Back  
**Guarantee**

**Vendor:**Cisco

**Exam Code:**300-375

**Exam Name:**Securing Wireless Enterprise Networks

**Version:**Demo

## QUESTION 1

The screenshot shows the Syslog Configuration page in a network management interface. On the left is a navigation menu with categories: Management, Summary, SNMP (General, SNMP V3 Users, Communities, Trap Receivers, Trap Controls, Trap Logs), HTTP-HTTPS, Telnet-SSH, Serial Port, Local Management Users, User Sessions, and Logs (Config, Message logs). The main content area is titled 'Syslog Configuration' and includes an 'Add' button for 'Syslog Server IP Address'. Below that is the 'Syslog Server' section with 'Syslog Level' set to 'Errors' and 'Syslog Facility' set to 'Local Use 0'. The 'Msg Log Configuration' section has 'Buffered Log Level' set to 'Errors', 'Console Log Level' set to 'Disable', and checkboxes for 'File Info' and 'Trace Info' both checked.

Refer to the exhibit. Which level message does the WLC send to the syslog server?

- A. syslog level errors and less severity messages
- B. syslog level error messages
- C. all syslog levels messages
- D. syslog level errors and greater severity messages

Correct Answer: D

---

## QUESTION 2

An engineer is deploying EAP-TLS as the authentication mechanism for an 802.1X-enabled wireless network. Which network device is responsible for applying the digital signature to a certificate to ensure that the certificate is trusted and valid?

- A. supplicant
- B. CA server
- C. wireless controller
- D. authentication server

Correct Answer: B

In cryptography, a certificate authority or certification authority (CA) is an entity that issues digital certificates. A digital certificate certifies the ownership of a public key by the named subject of the certificate. This allows others (relying parties) to rely upon signatures or on assertions made about the private key that corresponds to the certified public key. In this model of trust relationships, a CA is a trusted third party--trusted both by the subject (owner) of the certificate and by the party relying upon the certificate.

---

### QUESTION 3

An engineer is setting up a new unique NAD on a Cisco ISE. Which two parameters must be configured? (Choose two.)

- A. device hostname
- B. device password
- C. RADIUS fallback
- D. device IP address
- E. RADIUS shared secret

Correct Answer: AD

---

### QUESTION 4

When a supplicant and AAA server are configured to use PEAP, which mechanism is used by the client to authenticate the AAA server in Phase One?

- A. PMK
- B. shared secret keys
- C. digital certificate
- D. PAC

Correct Answer: C

---

### QUESTION 5



Refer to the exhibit. Which level message does the WLC send to the syslog server?

- A. syslog level errors and less severity messages
- B. syslog level errors messages
- C. all syslog levels messages
- D. syslog level errors and greater severity messages

Correct Answer: D

---

#### QUESTION 6

An engineer configures 802.1X authentication for the access points using the config `ap 802.1Xuser add username admin password secret ap_01` command. Which EAP method does the access point use to authenticate?

- A. LEAP
- B. EAP-TLS
- C. MS-CHAPv2 PEAP
- D. EAP-FAST

Correct Answer: D

Enables or disables Extensible Authentication Protocol-Flexible Authentication via Secure Tunneling (EAP-FAST) authentication. [https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-2/config-guide/b\\_cg82/b\\_cg82\\_chapter\\_01101111.html](https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-2/config-guide/b_cg82/b_cg82_chapter_01101111.html)

---

**QUESTION 7**

You have run some reports on Cisco Prime Infrastructure and want to download them. In which format must you download the reports?

- A. TXT
- B. XLSX
- C. HTML
- D. PDF

Correct Answer: D

Reference: [https://www.cisco.com/c/en/us/td/docs/net\\_mgmt/prime/infrastructure/3-4/user/guide/bk\\_CiscoPrimeInfrastructure\\_3\\_4\\_0\\_UserGuide/bk\\_CiscoPrimeInfrastructure\\_3\\_4\\_0\\_UserGuide\\_chapter\\_011000.html](https://www.cisco.com/c/en/us/td/docs/net_mgmt/prime/infrastructure/3-4/user/guide/bk_CiscoPrimeInfrastructure_3_4_0_UserGuide/bk_CiscoPrimeInfrastructure_3_4_0_UserGuide_chapter_011000.html)

---

**QUESTION 8**

An engineer has configured MAC filtering on an employee WLAN and wants clients that fail MAC filtering to attempt to be authenticated via the RADIUS server before denying network access. Which functionality must be enabled on the WLAN to achieve this goal?

- A. MAC authentication failover to 802.1X authentication
- B. EAP-TLS failover to 802.11r authentication
- C. WPA2 AES failover to RADIUS authentication
- D. 802.1x failover to WPA2 AES authentication

Correct Answer: A

Reference: [https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-8/config-guide/b\\_cg88/wlan\\_security.html](https://www.cisco.com/c/en/us/td/docs/wireless/controller/8-8/config-guide/b_cg88/wlan_security.html)

---

**QUESTION 9**

Which user role can access CMX Visitor Connect?

- A. Connect
- B. Power User
- C. Guest User
- D. Super Administrator

Correct Answer: D

Reference: [https://www.cisco.com/c/en/us/td/docs/wireless/mse/7-6/CMX\\_Dashboard/Guide/Cisco\\_CMX\\_Dashboard\\_C](https://www.cisco.com/c/en/us/td/docs/wireless/mse/7-6/CMX_Dashboard/Guide/Cisco_CMX_Dashboard_C)

### QUESTION 10

Which three options are valid client profile probes in Cisco ISE? (Choose three.)

- A. DHCP
- B. 802.1X
- C. CCX
- D. NetFlow
- E. TACACS
- F. HTTP

Correct Answer: ADF

Valid client probes in ISE are: NetFlow Probe DHCP Probe DHCP SPAN Probe HTTP Probe RADIUS Probe DNS Probe

Reference: [http://www.cisco.com/en/US/docs/security/ise/1.0/user\\_guide/ise10\\_prof\\_pol.html](http://www.cisco.com/en/US/docs/security/ise/1.0/user_guide/ise10_prof_pol.html)

---

### QUESTION 11

Which command is an SNMPv3-specific command that an engineer can use only in Cisco IOS XE?

- A. snmp-server user remoteuser1 group1 remote 10.12.8.4
- B. snmp-server host 172.16.1.33 public
- C. snmp-server community comaccess ro 4
- D. snmp-server enable traps wireless

Correct Answer: A

### SUMMARY STEPS

1.

enable

2.

configure terminal

3.

snmp-server group [group-name {v1 | v2c | v3 [auth | noauth | priv]]] [read read-view] [write write-view] [notify notify-view] [access access-list]

4.

```
snmp-server engineID {local engine-id | remote ip-address [udp-port udp-port-number] [vrf vrf-name] engine-id-string}
```

5.

```
snmp-server user user-name group-name [remote ip-address [udp-port port]] {v1 | v2c | v3 [encrypted] [auth{md5 | sha} auth-password]} [access access-list]
```

6.

end Reference: <http://www.cisco.com/c/en/us/td/docs/ios-xml/ios/snmp/configuration/xe-3se/3850/snmp-xe-3se-3850-book/nm-snmp-snmpv3.html#GUID-54F1E297-CE1D-45FE-9751-B8D129606010>

---

## QUESTION 12

An engineer is working on a remote site that is configured using FlexConnect. They are worried that the access points will not send RADIUS requests directly to the authentication server in standalone mode. Which command ensures direct authentication using the default ports as defined on the WLC?

- A. config flexconnect group Remote radius server acct add primary 10.10.10.10 1813 Cisco123
- B. config flexconnect group Remote radius server auth add primary 10.10.10.10 1813 Cisco123
- C. config flexconnect group Remote radius server acct add primary 10.10.10.10 1812 Cisco123
- D. config flexconnect group Remote radius server auth add primary 10.10.10.10 1812 Cisco123

Correct Answer: C

To Read the [Whole Q&As](#), please purchase the [Complete Version](#) from [Our website](#).

## Try our product !

100% Guaranteed Success

100% Money Back Guarantee

365 Days Free Update

Instant Download After Purchase

24x7 Customer Support

Average 99.9% Success Rate

More than 800,000 Satisfied Customers Worldwide

Multi-Platform capabilities - [Windows](#), [Mac](#), [Android](#), [iPhone](#), [iPod](#), [iPad](#), [Kindle](#)

## Need Help

Please provide as much detail as possible so we can best assist you.

To update a previously submitted ticket:



 <p><b>One Year Free Update</b> Free update is available within One Year after your purchase. After One Year, you will get 50% discounts for updating. And we are proud to boast a 24/7 efficient Customer Support system via Email.</p>	 <p><b>Money Back Guarantee</b> To ensure that you are spending on quality products, we provide 100% money back guarantee for 30 days from the date of purchase.</p>	 <p><b>Security &amp; Privacy</b> We respect customer privacy. We use McAfee's security service to provide you with utmost security for your personal information &amp; peace of mind.</p>
---	---	--

Any charges made through this site will appear as Global Simulators Limited.

All trademarks are the property of their respective owners.